



The right to any changes as may be technically or legally required is reserved.

technical specifications HSK-RA 102

width (mm)	925
length (mm)	1767
height (mm)	1426
width with cover panel (mm)	890
length with cover panel (mm)	1635
height with cover panel (mm)	1536
water content (l)	360
weight (kg)	1470
heating surface (m ²)	10,50
heating output (kW)	0-96
rated heat output (kW)	96
CO ² (%)	10,00
efficiency (%)	>90
flue gas mass flow (kg/Sek.)	0.085000
flue gas temperature (°C)	180
flue depress (Pa)	30
flue depress with fgb (Pa)	15
flue depress with underpressure control (Pa)	10
pressure drop at dT 10K (mbar)	15,90
heat flow (Zoll)	1 1/2
heat return (Zoll)	1 1/2
safety flow (Zoll)	1
safety return (Zoll)	1
filling and draining (Zoll)	1/2
safety cooling inlet (Zoll)	1
safety cooling outlet (Zoll)	1
sensor safety valve (Zoll)	1/2
flue gas pipe Ø (mm)	250
power supply	400V/16A 5polig
min. volume flow rate for return flow boot at 15K (m ³ /h)	1,91

technical specifications HSK-RA 102

Stand 29.04.2011

Fa. Heizomat GmbH - Gerätebau / Energiesysteme - 91710 Gunzenhausen - DT Maicha 21 - 09836/9797-0