



the right to any changes as may be technically or legally required is reserved.

technical specifications RHK-AK 304

width (mm)	1695 (1692)
length (mm)	3030
height (mm)	1925 (1779)
width with cover panel (mm)	1880
length with cover panel (mm)	3490
height with cover panel (mm)	2035
water content (l)	1258
weight (kg)	5400
heating surface (m ²)	29,70
heating output (kW)	*270 / **240
rated heat output (kW)	0 - 300
CO ² (%)	10,00
efficiency (%)	>90
flue gas mass flow (kg/Sek.)	0.250000
flue gas temperature (°C)	180
flue depress (Pa)	-
flue depress with fgb (Pa)	24
flue depress with underpressure control (Pa)	10
pressure drop at dT 10K (mbar)	126,90
max. pressure (bar)	3
heat flow (DN)	80
heat return (DN)	80
safety flow (Zoll)	1 1/2
safety return (Zoll)	1 1/2
filling and draining (Zoll)	1 1/4
safety cooling inlet (Zoll)	-
safety cooling outlet (Zoll)	-
sensor safety valve (Zoll)	-
flue gas pipe Ø (mm)	300
min. opening for air supply (cm ²)	650
power supply	400V/32A 5polig
min. volume flow rate for return flow boot at 15K (m ³ /h)	5,73

technical specifications RHK-AK 304

Stand 29.04.2011

Fa. Heizomat GmbH - Gerätebau / Energiesysteme - 97110 Gunzenhausen - OT Maicha 21 - 09836/9797-0