



### Electrical connection data Boilers up to 101 kW

Connection	400V / 3N PE CEE plug 16A
Protection	C 16A
RCD switch	Type A IΔN 30mA

### Technical data HSK-RA 40 without e-filter

transport width (mm)	775
transport length (mm)	1267
transport height (mm)	1392
width with cover panel (mm)	775
length with cover panel (mm)	1135
height with cover panel (mm)	1442
water content (l)	210
weight (kg)	860
heat exchanger surface (m <sup>2</sup> )	4,90
continuous heat load (kW)	0-40
heating output (kW)	40
CO <sup>2</sup> (%)	10,0
efficiency (%)	>90
flue gas mass flow (kg/s)	0,043700
flue gas temperature (°C)	180
flue depress (PA)	10
flue depress with underpressure monitoring (PA)	10
drop at dT 10 pressure K (mbar)	14,80
max. pressure (bar)	3
flow heat (inch)	1 1/2
heat return (inch)	1 1/2
safety flow (inch)	1
safety return (inch)	1
filling and emptying (inch)	1/2
thermowell (inch)	1/2
flue gas pipe diameter (mm)	200
min. opening for air supply (cm <sup>2</sup> )	150
min. volume flow rate for return temp. increase at 15K (m <sup>3</sup> /h)	0,85

The boiler should be accessible from three sides. The discharging system should not cross the heating room.  
 Room height and position of the e-filter should be discussed with the Heizomat team.  
 Connecting points for the necessary potential equalization on the boiler see supplementary sheet  
 "Connection of the Heizomat boiler system to the main potential equalization of a building".

Technical changes that serve the permanent further development remain reserved.

Status 01.07.2017

**Heizomat**

Heizomat GmbH Gerätebau- Energiesysteme  
 Maicha 21 - 91710 Gunzenhausen - 09836/9797-0